

TABULKA ŠACHET DEŠŤOVÉ KANALIZACE - ETAPA 1

| Stoka | Šachta | Kóta poklopu | Kóta dna | Hloubka šachty | Poklop + rám | Skruž 250 | Skruž 500 | Skruž kónická | Zákryt. deska | Vyrovnávací prstenec | | | | | Dno DN STOKY | Pozn. |
|-------|--------|--------------|----------|----------------|--------------|-----------|-----------|---------------|---------------|----------------------|-----|----|----|----|-----------------|--------|
| | | | | | | | | | | 120 | 100 | 80 | 60 | 40 | | |
| DA | ŠDA1 | 463.400 | 460,57 | 2.83 | 1 | 1 | 2 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | DN 300 | + D2 |
| | ŠDA2 | 464.700 | 463,20 | 1.50 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | |
| | ŠDA3 | 466.600 | 465,10 | 1.50 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | |
| | ŠDA4 | 470.190 | 468,69 | 1.50 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | + D3 |
| | ŠDA5 | 471.300 | 469,80 | 1.50 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | |
| D0 | ŠD0.1 | 462.500 | 460,20 | 2.30 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 500 | +D5 |
| | ŠD0.2 | 463.050 | 460,65 | 2.40 | 1 | 0 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | DN 500 | |
| | ŠD0.3 | 464.830 | 462,45 | 2.38 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | DN 500 | |
| | ŠD0.4 | 466.270 | 464,00 | 2.27 | 1 | 1 | 0 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | DN 500 | |
| | ŠD0.5 | 466.680 | 464,28 | 2.40 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | DN 500 | |
| | ŠD0.6 | 467.750 | 464,64 | 3.11 | 1 | 1 | 2 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | DN 500 | |
| | ŠD0.7 | 467.360 | 465,00 | 2.36 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | DN 500 | |
| | ŠD0.8 | 468.030 | 465,65 | 2.38 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | DN 500 | |
| | ŠD0.9 | 469.750 | 467,45 | 2.30 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 500 | |
| D1 | ŠD1.1 | 469.170 | 467,10 | 2.07 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | DN 250 | + UV28 |
| | ŠD1.2 | 472.290 | 469,72 | 2.57 | 1 | 0 | 2 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | DN 250 | |
| | ŠD1.3 | 473.880 | 471,75 | 2.13 | 1 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | DN 250 | |
| D5 | ŠD5.1 | 466.230 | 464,09 | 2.14 | 1 | 0 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | DN 300 | |
| | ŠD5.2 | 468.850 | 466,25 | 2.60 | 1 | 0 | 2 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | DN 300 | |
| | ŠD5.3 | 468.850 | 466,50 | 2.35 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | DN 300 | |
| | ŠD5.4 | 469.120 | 466,90 | 2.22 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | DN 300 | |
| | ŠD5.5 | 472.510 | 470,18 | 2.33 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | DN 300 | |
| | ŠD5.6 | 474.710 | 472,59 | 2.12 | 1 | 0 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | DN 300 | |
| Σ | | | | | 23 | 5 | 22 | 23 | 0 | 3 | 7 | 6 | 5 | 3 | | |

Před provedením vrchního krytu komunikace ověřit/upravit vyrovnávací prstence
Spoje prvků šachty budou opatřeny těsněním

TABULKA ŠACHET JEDNOTNÉ KANALIZACE - ETAPA 1

| Stoka | Šachta | Kóta poklopu | Kóta dna | Hloubka šachty | Poklop + rám | Skruž 250 | Skruž 500 | Skruž kónická | Zákryt. deska | Vyrovnávací prstenec | | | | | Dno DN STOKY | Pozn. |
|-------|---------|--------------|----------|----------------|--------------|-----------|-----------|---------------|---------------|----------------------|-----|----|----|----|-----------------|------------------|
| | | | | | | | | | | 120 | 100 | 80 | 60 | 40 | | |
| J0 | ŠJ0.1 | 467.220 | 465,72 | 1.50 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | + lok. Za Školou |
| | ŠJ0.2 | 467.940 | 466,19 | 1.75 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | |
| | ŠJ0.3 | 469.390 | 467,14 | 2.25 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | |
| | ŠJ0.4 | 470.400 | 468,20 | 2.20 | 1 | 0 | 1 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | DN 300 | |
| | ŠJ0.5 | 471.790 | 469,48 | 2.31 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | DN 300 | |
| J5 | ŠJ5.1 | 462.990 | 461,39 | 1.60 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | DN 300 | koncová |
| | ŠJ5.2 | 466.400 | 463,57 | 2.83 | 1 | 1 | 2 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | DN 300 | |
| | ŠJ5.3 | 468.900 | 465,80 | 3.10 | 1 | 0 | 3 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | DN 300 | |
| | ŠJ5.4 | 468.880 | 466,30 | 2.58 | 1 | 0 | 2 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | DN 300 | |
| | ŠJ5.5 | 469.060 | 466,38 | 2.68 | 1 | 0 | 2 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | DN 300 | |
| | ŠJ5.6 | 471.400 | 469,15 | 2.25 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | DN 300 | |
| | ŠJ5.7 | 473.970 | 471,66 | 2.31 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | DN 300 | |
| J5.1 | ŠJ5.1.1 | 471.930 | 469,69 | 2.24 | 1 | 0 | 1 | 1 | 0 | 2 | 0 | 0 | 0 | 0 | DN 300 | koncová |
| | ŠJ5.1.2 | 473.360 | 471,14 | 2.22 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | DN 300 | |
| | ŠJ5.1.3 | 474.720 | 472,60 | 2.12 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | DN 300 | |
| Σ | | | | | 15 | 6 | 17 | 15 | 0 | 3 | 6 | 4 | 2 | 1 | | |

Před provedením vrchního krytu komunikace ověřit/upravit vyrovnávací prstence
Spoje prvků šachty budou opatřeny těsněním

